

NASA TECH BRIEF

Ames Research Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Subminiature Micropower Digital Recorder

The problem:

To provide a low-power subminiature recorder capable of recoding high-density digital data that are collected periodically or randomly from a multiplicity of sensors.

The solution:

Energize a magnetic recording head (or selectively energize a multiplicity of heads) with suitable pulsatile signals to reverse the polarization on magnetically-sensitive tape *while the tape is immobilized* at the recording head and then, prior to the next recording, step the tape so that a new area of tape is at the recording head.

How it's done:

Two commercially available 4-track magnetic recording heads are built into a recorder system that includes the following: (a) a pulsed magnetic motor drive which steps the tape 25.4 μm per pulse by a ratchet wheel arrangement; (b) a reel arrangement with a capacity of approximately 64 m of nominal 6.35- μm thick polyester-base magnetic tape; (c) a tape take-up mechanism; (d) suitable electrical plug arrangements for feeding electrical signals to the recording head and to the tape drive motor. The prototype device weighs 110 grams and has a volume of approximately 100 ml.

The tape loaded on the reel is prepolarized in the N-S direction through the tape. A recording pulse of suitable polarity on any recording track reverses the magnetic polarization on the tape at the recording

head; when recording takes place, the tape is not moving. At the time of playback, the recorded area of polarization is read out as a recorded pulse.

In the prototype recorder, with 8 channels, storage capacity is calculated as follows: For a tape length of 64 m, or $64 \times 10^6 \mu\text{m}$, there are $64 \times 10^6 / 25.4 = 2.52 \times 10^6$ recording pulses, and $2.52 \times 10^6 \text{ pulses} \times 8 \text{ channels} = 20.16 \times 10^6 \text{ bits}$. The capacity in words is 2.52×10^6 when a single word is defined as a row of 8-bit spaces.

To reverse magnetic polarization local to the recording head on the 6.35- μm thick tape, the optimum pulse is 0.15 volt with a duration of 225×10^{-8} second. Measurements indicate that a single recording pulse consumes 21×10^{-6} watt of electrical power; hence, if the tape were entirely filled with recorded bits (an extreme situation), the total energy required to make such a recording is 0.09 joule. If such data were accumulated over a period of one year, average power consumption for recording would be 2.9×10^{-9} watt. If a recording-pulse circuit efficiency of only 25% is assumed, total time-current requirement for the recording pulse circuitry would be 0.6 milliampere-hour.

The magnetic motor drive for the recorder requires an electrical pulse of 2.7 volts for a duration of about 20 msec; measurements indicate a power consumption for each pulse of 125×10^{-8} watt. Again assuming a pulse-generating efficiency of only 25%, total time-current requirements for the drive motor pulse (2.52×10^6 steps in tape position) would be 3300 milliampere-hours.

(continued overleaf)

Note:

Requests for further information may be directed
to:

Technology Utilization Officer
Ames Research Center
Moffett Field, California 94035
Reference: TSP 73-10491

Patent status:

NASA has decided not to apply for a patent.

Source: Robert M. Goodman and
Richard W. Pitman of
The Franklin Institute Research Laboratories
under contract to
Ames Research Center
(ARC-10746)